




PJM03N60SQ

N-Channel Enhancement Mode Power MOSFET

Product Summary

- $V_{DS} = 60V, I_D = 3A$
- $R_{DS(on)} < 95m\Omega @ V_{GS} = 10V$
- $R_{DS(on)} < 110m\Omega @ V_{GS} = 4.5V$

SOT-89



(Top View)

Features

- Advanced Trench Technology
- RoHS and Reach Compliant
- Halogen and Antimony Free
- Moisture Sensitivity Level 1



Application

- DC/DC Converter
- Battery Switch

Pin	Description
1	Gate
2	Drain
3	Source

Schematic Diagram

Marking Code



Absolute Maximum Ratings

Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	3	A
Drain Current-Pulsed ^{Note1}	I_{DM}	18	A
Maximum Power Dissipation	P_D	1.5	W
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{STG}	-55 to +150	°C

Thermal Characteristics

Thermal Resistance, Junction-to-Ambient ^{Note2}	$R_{\theta JA}$	83	°C/W
----------------------------------------------------------	-----------------	----	------



PJM03N60SQ

N-Channel Enhancement Mode Power MOSFET

Electrical Characteristics


(Ta=25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250μA	60	--	--	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =60V, V _{GS} =0V	--	--	1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
Gate Threshold Voltage ^{Note3}	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1	1.5	2.5	V
Drain-Source On-Resistance ^{Note3}	R _{DS(on)}	V _{GS} =10V, I _D =3A	--	68	95	mΩ
		V _{GS} =4.5V, I _D =3A	--	80	110	mΩ
Forward Transconductance ^{Note3}	g _{FS}	V _{DS} =5V, I _D =1A	--	3	--	S
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1MHz	--	350	--	pF
Output Capacitance	C _{oss}		--	29	--	pF
Reverse Transfer Capacitance	C _{rss}		--	23	--	pF
Total Gate Charge	Q _g	V _{DD} =30V, I _D =3A, V _{GS} =0~10V	--	9	--	nC
Gate-Source Charge	Q _{gs}		--	1.5	--	nC
Gate-Drain Charge	Q _{gd}		--	2	--	nC
Switching Characteristics						
Turn-on Delay Time	t _{d(on)}	V _{DD} =30V, I _D =2A V _{GS} =10V, R _{GEN} =3Ω	--	5	--	nS
Turn-on Rise Time	t _r		--	7	--	nS
Turn-off Delay Time	t _{d(off)}		--	37	--	nS
Turn-off Fall Time	t _f		--	22	--	nS
Source-Drain Diode Characteristics						
Diode Forward Voltage ^{Note3}	V _{SD}	V _{GS} =0V, I _S =3A	--	--	1.2	V
Diode Forward Current ^{Note2}	I _S		--	--	3	A







Note: 1. Repetitive Rating: Pulse width limited by maximum junction temperature.

2. Surface Mounted on FR4 Board, t ≤ 10 sec.

3. Pulse Test: Pulse width≤300μs, duty cycle≤0.5%.





Typical Characteristic Curves





PJM03N60SQ
N-Channel Enhancement Mode Power MOSFET






Package Outline

SOT-89

Dimensions in mm




Ordering Information

Device	Package	Shipping
PJM03N60SQ	SOT-89	1,000PCS/Reel&7inches
		3,000PCS/Reel&13inches



Conditions of Soldering and Storage

◆ Recommended condition of reflow soldering



Recommended peak temperature is over 245 °C. If peak temperature is below 245 °C, you may adjust the following parameters:

- Time length of peak temperature (longer)
- Time length of soldering (longer)
- Thickness of solder paste (thicker)

◆ Conditions of hand soldering

- Temperature: 370 °C
- Time: 3s max.
- Times: one time

◆ Storage conditions

- **Temperature**
5 to 40 °C
- **Humidity**
30 to 80% RH
- **Recommended period**
One year after manufacturing




PJM03N60SQ


N-Channel Enhancement Mode Power MOSFET

Package Specifications


- The method of packaging (1,000PCS/Reel&7inches)




◆ Embossed tape and reel data




symbol	Value(unit:mm)
A	$\Phi 179 \pm 1$
B	60.5 ± 0.2
C	15.3 ± 0.3
D	12.5~13.7
E	$\Phi 13.5 \pm 0.2$
F	$\Phi 10.0 \pm 0.2$
G	2.7 ± 0.2
T1	1.0 ± 0.2






Package Specifications

- The method of packaging (3,000PCS/Reel&13inches)



◆ Embossed tape and reel data



symbol	Value(unit:mm)
A	$\phi 330 \pm 1$
B	12.7 ± 0.5
C	16.5 ± 0.3
D	$\phi 99.5 \pm 0.5$
E	$\phi 13.6 \pm 0.3$
F	2.8 ± 0.3
T	1.9 ± 0.2

